GUIDE TO STATE AND FEDERAL REQUIREMENTS FOR EMPLOYEE / MIGRANT HOUSING





PREPARED JOINTLY BY:

DEPARTMENT OF HOUSING AND COMMUNITY DEVELOPMENT DIVISION OF CODES AND STANDARDS

AND

UNITED STATES DEPARTMENT OF LABOR WAGES AND HOUR DIVISION

HCD EH 30 (Rev. 08/20)

CONTENTS	200	INTRODUCTION
		This guide was developed jointly by the U.S. Department of Labor, Wage and Hour Division (DOL-
Introduction Sources of Additional Information 2		WHD) and the California Department of Housing and Community Development, Division of Codes and
Sources of Additional Information		Standards (HCD). The purpose of the guide is to provide basic information to employee housing
Housing Standards Requirements For 3		providers on the most restrictive housing requirements of the Federal and California laws and regulations
Employee/Migrant Housing		that govern maintenance, use, and occupancy standards of living quarters for employees, primarily agricultural workers.
Caretakers		ugiivatuitii workois.
Communicable Diseases 4		The information is based on laws and regulations in effect at the time this guide was printed. Should any
4		of the information or requirements stated be superseded by changes in law and regulation, this publication likewise is superseded. The information is general and is not to be considered in the same
Construction and Repair Cooking, Kitchen, and Mess Halls		light as official statements of positions contained in Interpretive Bulletins published in the Federal
1		Register and the Code of Federal Regulations, in the official opinion letters of the Wage and Hour
Electrical 5		Division, or any official publication of HCD.
Enforcement and Penalties 5		State of California summaries were derived from the California Health and Safety Code (HSC), Division
Fire Safety First Aid		13, Part 1, Section 17000 through 17062, known as the Employee Housing Act, the California Code of
First Aid 0]	Regulations (CCR), Title 25, Division 1, Chapter 1, Sections 600 through 940, and the California Code
Garbage and Refuse 6		of Regulations, Title 24, the California State Building Code. The user of the guide should be aware that
		other California statutes and regulations not referenced may be applicable to employee housing.
Hand Washing, Bathing, and Laundry		The State of California Employee Housing Act applies to two types of employee housing: (1) living
Heating 8		quarters provided for five (5) or more employees by the employer; and (2) housing accommodations or
Housing Site		structures in specified rural provided for five (5) or more agricultural workers employed on a temporary, seasonal, or permanent basis, not maintained in connection with any work place.
Housing ou acture		seasonal, of permanent basis, not maintained in connection with any work place.
Insects and Rodents 11	_	Federal summaries were derived from the Occupational Safety and Health Act (OSHA) regulations
Lighting 11	-	found in Title 29, Code of Federal Regulations, Part 1910.142 and the Migrant and Seasonal Agricultural Worker Protection Act (MSPA) found in Title 29, Code of Federal Regulations Part 500. Housing
Liquid Propane (LP) Gas Mobilehomes, Recreational Vehicles		providers who constructed labor camps prior to April 1980 and relied on Federal standards in effect prior
iviodilenomes, Kecreational Vehicles		to April 3, 1980, should contact the nearest Wage and Hour Division Office for guidance.
12	2	The Federal MCDA regulations are tract and account and account to the state of the
and Grower eight Modulars 13	•	The Federal MSPA regulations protect migrant and seasonal agricultural workers in their dealings with farm labor contractors (FLCs), agricultural employers, agricultural associations, and providers of
Posting of Required Information 13		migrant housing. Health and safety regulations enforced under MSPA apply to temporary migrant
Screens 13	5 1	housing regardless of the number of migrant or seasonal workers living there.
Sewage 13		The major part of this guide, "Housing Standards Requirements For Employee/Migrant Housing"
		chart, contains a summary of the Federal and California requirements for safe and sanitary
Tents 14	4	housing conditions. The chart is printed side-by-side for comparison purposes and contains a
Toilets 14		subject column, a statutory and/or regulatory code authority column with brief summaries of
Water Supply 15		statutory and/or regulatory language. The most restrictive language is designated by the pointed arrow (◀) symbol. Operators of farmworker housing must comply with the most restrictive
		requirements to ensure compliance with both Federal and California requirements.

SOURCES OF ADDITIONAL INFORMATION

More specific information can be obtained by:

1. Review of the following reference documents at law and public libraries:

- California Health and Safety Code, Division 13, Part 1, beginning with Section 17000.
- California Code of Regulations, Title 25, Chapter 1, beginning with Section 600.
- California Code of Regulations, Title 24, California State Building Code.
- Federal Migrant and Seasonal Agricultural Worker Protection Act
- Code of Federal Regulations, Title 29, Parts 500 through 500.270.
- Code of Federal Regulations, Title 29, Part 1910.142 (OSHA Reg.)

2. Obtaining or purchasing copies of documents as follows:

• <u>CALIFORNIA HEALTH AND SAFETY CODE, DIVISION 13, PART 1</u> (Employee Housing Act) can be purchased from:

West Publishing Company, PO Box 64526, St. Paul, MN; telephone 800-328-4880.

• CALIFORNIA CODE OF REGULATIONS, TITLE 25, CHAPTER 1, and the CALIFORNIA CODE OF REGULATIONS, TITLE 24.

Can be purchased from:

Barclays Law Publishers, Attention: CCR/Agency Services Representative 400 Oyster Point Blvd., PO Box 3006, South San Francisco, CA. 94083 800-888-3600 or on the internet at http://www.leginfo.ca.gov/calaw.html

 MIGRANT AND SEASONAL AGRICULTURAL WORKERS PROTECTION ACT and OSHA REGULATION 1910.142.

Can be obtained by contacting the Wage and Hour Division of the U.S. Department of Labor offices as shown on this page or on the internet at, http://www.dol.gov/esa/whd/mspa/index.htm

3. Contacting the appropriate government offices listed below:

If the housing is located in one of the following counties contact the county office listed below:

Monterey

Environmental Health 1270 Natividad Road Salinas, CA 93906 (831) 755-4539

Napa

Department of Environmental Management 1195 Third Street, Room 210 Napa, CA 94559 (707) 253-4471

Sacramento

Environmental Mgmt. Dept. 10590 Armstrong Ave., Suite B Mather, CA. 95655 (916) 875-8444

San Mateo

Environmental Health Services 2000 Alameda de las Pulgas, Ste. 100 San Mateo, CA 94403 (650) 372-6200

Stanislaus

Dept. of Environmental Resources 3800 Cornucopia Way, Ste. C Modesto, CA 95358-9492 (209) 525-6700

San Joaquin

Environmental Health Dept. 1868 East Hazelton Avenue Stockton, CA 95205 (209) 468-3912

Santa Cruz

Environmental Health Services 701 Ocean Street, Rm 312 Santa Cruz, CA 95060 (831) 454-2022

Tulare

Resource Management Agency 5961 S. Mooney Blvd Visalia, CA 93277-9394 (559) 624-7000

STATE OF CALIFORNIA DEPARTMENT OF HOUSING AND COMMUNITY DEVELOPMENT DIVISION OF CODES AND STANDARDS

NORTHERN CALIFORNIA:

(North of Fresno County) 9342 Tech Center Dr #550 Sacramento, Ca. 95826 (800) 952-8356

SOUTHERN CALIFORNIA

(South of Madera County) 3737 Main Street, Ste 400 Riverside, CA 92501 (800) 952-8356

U.S. DEPARTMENT OF LABOR WAGE & HOUR DIVISION

LOS ANGELES

300 South Glendale Ave., 400 Glendale, CA. 91205-1752 (818) 240-5274/75

WEST COVINA

100 North Barranca St., 850 West Covina, CA. 91791 (626) 966-0478

SAN DIEGO

5675 Ruffin Rd, 320 San Diego, CA. 92123-1362 (619) 557-5606

SAN FRANCISCO

455 Market St., 800 San Francisco, CA. 94105 (415) 744-5590

SACRAMENTO

2800 Cottage Way, Rm. W-1836 Sacramento, CA. 95825-1886 (916) 978-6123

HOUSING STANDARDS REQUIREMENTS FOR EMPLOYEE/MIGRANT HOUSING

SC 17038 526, 627 738 al OSHA Reg. 42(1)	A responsible person must be assigned by the operator to maintain the buildings and surrounding areas. Cooks for central mess halls must be certified by local health departments.	 ✓ Use state standard. ✓ Equal to State standard. In addition Caretakers must report any communicable diseases, outbreak of food poisoning, and prevalent illnesses, such as jaundice, hepatitis,
al OSHA Reg. 42(1)		In addition Caretakers must report any communicable diseases, outbreak of food poisoning, and
552		etc., to the local health department.
	All new construction and repairs must meet current building codes and standards or standards that were in effect when they were constructed. Contact the local building department for information and permits.	■ Equal to State standard.
736-742 al OSHA Reg. 42(i), 1910.142(b)(9), 42(b)(10)	KITCHENS: Kitchens, when provided, must be of adequate size and proper construction. Cooking areas must be clean and sanitary at all times. Refrigeration capable of maintaining a temperature of 45° F or below must be provided. Sufficient shelving space to store food supplies off the floor must be provided. Floors, walls, ceilings, tables, shelves, and counter tops must be made of cleanable materials and maintained in a clean and sanitary condition. (Also, see "Heating") MESS HALLS: Mess halls must be certified by the local health	 ✓ KITCHENS: Equal to State standard. In addition Stoves provided must be at a ratio of not less than one stove to ten occupants or one stove to two families. ✓ MESS HALLS: Equal to State standard.
a	OSHA Reg. (2(i), 1910.142(b)(9),	standards that were in effect when they were constructed. Contact the local building department for information and permits. KITCHENS: KITCHENS: Kitchens, when provided, must be of adequate size and proper construction. Cooking areas must be clean and sanitary at all times. Refrigeration capable of maintaining a temperature of 45° F or below must be provided. Sufficient shelving space to store food supplies off the floor must be provided. Floors, walls, ceilings, tables, shelves, and counter tops must be made of cleanable materials and maintained in a clean and sanitary condition. (Also, see "Heating") MESS HALLS:

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
ELECTRICAL	CCR 850-896 Federal OSHA Reg. 1910.142(g) Federal MSPA Reg. 500.134	Electrical equipment, devices, safeguards and service equipment must be maintained as follows: • good working order • secured in an approved manner when in use • protected from weather Fuses or circuit breakers must by used to protect electrical conductors. Grounding is required for fixed noncurrent carrying metal parts of electrical equipment. Grounded cords must be used with appliances such as washing machines and electrical systems of gas stoves. Outlets located adjacent to fixed appliances, lavatories, sinks, laundry tubs or within reach of a grounded surface must be in good working order. For lighting requirements see page 11.	■ Equal to State and local building codes.
ENFORCEMENT AND PENALTIES	CA HSC 17037, 17050, 17054, 17060, 17061, 17061.5, 17061.7, 17061.9 17062 Federal MSPA Reg. 500.140 – 500.146	The Employee Housing Act establishes authority for inspections, investigations and punitive action as follows: • suspension of a permit to operate • assessment of penalties • issuance of citations with civil penalties • civil action for an award of civil penalties (monetary) • criminal prosecution to obtain imprisonment The Employee Housing Act is enforced by HCD, except where local government assumes enforcement responsibility. Tenants/workers also may seek judicial remedies.	The Migrant and Seasonal Agricultural Worker Protection Act (MSPA) establishes authority for inspections, investigations, and punitive action as follows: • revocation of Federal permit • assessment of civil money penalties up to \$1,000 per violation • criminal prosecution to obtain imprisonment and/or monetary fines The Migrant and Seasonal Agricultural Worker Protection Act is enforced by DOL-WHD. Tenants/workers also may seek judicial remedies.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
FIRE SAFETY	CCR 744, 746 Federal MSPA Reg. 500.134	Mess hall kitchens: Approved Class B-C extinguisher; minimum size 20 units Dormitories: Approved Class A extinguisher; minimum size 2 units per 5000 square feet of floor area No article or material that the enforcement agency determines to be a fire hazard will be maintained in or on the premises of employee housing.	◄ Equal to State standards.
FIRST AID	Federal OSHA Reg. 1910.142(k)	Use Federal standards	First aid facilities must be maintained and made available. A person trained to administer first aid must oversee first aid facilities.
GARBAGE AND REFUSE	CCR 742 Federal OSHA Reg. 1910.142(h), 1910.142(a)(4) 1910.142(i)	Use Federal standards ▶	 Garbage containers must be: fly and rodent resistant, cleanable, plus single service containers must be provided on a metal or concrete stand provided at a ratio of one container for each family or unit within 100 feet of shelter equipped with tight fitting lids when located in a kitchen emptied when full, but not less than twice a week

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
HAND WASHING, BATHING, AND LAUNDRY	CCR 760, 762, 764, 766, 768, 774, 788, 790, 792 Federal OSHA Reg. 1910.142(f)	HOT AND COLD RUNNING WATER MUST BE PROVIDED FOR BATHING. HAND WASHING: Lavatories must be located adjacent to toilet facilities. Use Federal standard.	HOT AND COLD RUNNING WATER MUST BE PROVIDED FOR HAND WASHING, BATHING AND LAUNDRY. HAND WASHING (lavatories): Basins must be provided at a ratio of one basin to every six occupants and/or one for each family unit.
		BATHING:	■ Bathing: Equal to State standards.
		 One bathing facility must be provided for each 10 occupants of each sex when constructed after February 22, 1973. Employee housing constructed prior to February 22, 1973 must provide one bathing facility for each 15 occupants of each sex. Bathing facilities must be clearly identified for "Men" or "Women". The use of proper symbols will be permitted. Showers must have adequate floor drains with walls and floors constructed of cleanable, noncorrosive and nonabsorbent waterproof materials. 	In addition Shower heads to be provided at a ratio of one for every 10 occupants.
		LAUNDRY: Clothes washing machines, when provided must be maintained with proper vents and drains.	 Laundry tray is required at a ratio of one to every 30 occupants. Facilities for drying clothes must be provided (clothesline).

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
HEATING	CCR 800-838 Federal OSHA Reg. 1910.142(b)(11), 1910.142(f)(4)	Heating equipment is not required, except in shower rooms, unless it is necessary to maintain a mean temperature of 70° F during occupancy. Heating and cooking equipment must be maintained and equipped as follows: • good working order • clean and free of grease • vented • shut-off valve must be provided for gas heating appliances Gas hot plates, cook stoves and ranges cannot be used as room heaters. Clearances between the heating appliance and combustible materials must be maintained as follows: • solid or liquid fuel radiant heaters-36 inches • solid or liquid fuel circulating heaters-12 inches • gas circulating space heaters-6 inches Open space under heating appliance must be a minimum of 4 inches. Combustible floors must be protected with sheet metal, extending a minimum of 6 inches on all sides and 18 inches at the front or side where ashes are removed.	■ Equal to State standards.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
HOUSING SITE	CCR 700-704, 710 Federal OSHA Reg. 1910.142 (a)	DRAINAGE: Premises must be free from depressions. Areas such as natural sinkholes and swamps within 200 feet of housing sites must be drained or filled. Irrigation drain ditches must be treated to prevent the breeding of mosquitoes, vermin, or vectors as approved by the local health department. LIVESTOCK: Domestic animals and poultry cannot be permitted to run freely through camp areas. MAINTENANCE: Buildings and surrounding areas	 ✓ DRAINAGE: Equal to State standards. <u>In addition</u> Drainage cannot endanger any domestic or public water supply. LIVESTOCK: No livestock can be quartered within 500 feet of housing structures. ✓ MAINTENANCE: Equal to State standards.
		must be kept safe, in a sanitary condition, in good working order, and free of rubbish, debris, and poisonous plants.	
HOUSING STRUCTURE	CCR 708-734, 736	GENERAL	▼ Equal to State standards
	CCR Title 24	Buildings must protect occupants from elements, be in good repair, safe and sanitary.	
	Federal OSHA Reg. 1910.142(a), 1910.142 (b), 1910.142 (d) and 1910.142(f)	Names or numbers must be clearly displayed to identify each building.	
	12101112(1)	FLOORS: Kitchen floors must be covered with cleanable, moisture resistant material.	FLOORS: Floors must be constructed of wood, asphalt, or concrete.
			Wood flooring must be elevated at least one foot from ground, and be of smooth, tight construction.
		WINDOWS: All living quarters must have windows with size minimally equal to 10 percent of usable floor	▼ WINDOWS: Equal to State standards.
		space and must be able to open at least one half way for ventilation.	In addition
		ioi ventuation.	Toilet rooms must have at least a six square foot window or similar ventilation.
		CEILINGS: Must be minimum average of 7 feet high.	◄CEILINGS: Equal to State standards.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
HOUSING STRUCTURE (continued)	CCR 708-734, 736 CCR Title 24 Federal OSHA Reg. 1910.142(a), 1910.142 (b), 1910.142 (d) and 1910.142(f)	ROOMS: Kitchen and mess halls: Must be of adequate size and properly constructed. Cannot be used for sleeping purposes.	◄ Kitchens and mess halls: Equal to State standards
	15100112(1)	Toilet and bathing facilities: Separate toilet room and bathing facilities required with adjacent lavatories.	Toilet and bathing facilities: Toilet rooms must be accessible without passing through sleeping room.
		SLEEPING FACALITIES: Sleeping room: Must be separated from other living space with at least 50 square feet of floor space for each occupant.	▼ Equal to State Standards
		Beds: A suitable, separate bed, constructed of sturdy and comfortable material must be provided to each occupant.	Beds: A clean bed, cot or bunk must be provided to each occupant.
		In addition	
		Occupants must be supplied with bedding upon request. A reasonable charge is allowed. This bedding must be maintained in a clean and sanitary manner.	
		Spacing of single beds: Use Federal standards ▶	Spacing of single beds: • 3 feet between beds • 1 foot above floor
		Spacing of bunk beds:	■ Bunk beds: Equal to State standards
		• 4 feet between beds	
		• 30 inches between lower and upper bunk.	
		• triple beds are not allowed	
		Storage: Use Federal standards	Storage: Storage facilities such as lockers must be provided in rooms.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
INSECTS AND RODENTS	CCR 704 Federal OSHA Reg. 1910.142(j)	Shelter must be free of vermin, vectors, and other matter of an infectious or contagious nature.	▼ Equal to State standards.
LIGHTING	CCR 872, 874, 880, 882, 884 Federal OSHA Reg. 1910.142(g)	 At least one convenience outlet and one light fixture. Bathroom and toilets: at least one light fixture Light fixtures over tub or shower must be moisture proof, with enclosure and gaskets, and in good condition. Switches for tub or shower lighting or fan, must be in dry location outside tub or shower space. Pull chain switches must not be maintained in damp location, and not over or within reach of a plumbing fixture, cook stove, range, furnace, and other grounded surface, such as concrete floors. 	▼ Equal to State standards.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
LIQUID PROPANE (LP) GAS	CCR 806-816 Federal MSPA Reg. 500.134	 LP tanks or cylinders cannot be located inside housing units or within 5 feet of an ignition source. Outlet must be 5 feet or more from any building opening lower than the outlet. LP tanks and cylinders cannot be stored under any housing unit. Clearance requirements from nearest building, mobilehome, or recreational vehicle are as follows: Minimum clearance of 10 feet for 61 to 576 gallon tanks 25 feet for 576 to 2000 gallon tanks SAFETY: LP tanks located adjacent to driveways and parking areas must be maintained to prevent mechanical damage. NO SMOKING signs must be displayed on all LP tanks. LP tanks must be positioned on a firm pad or foundation. Existing gas supply tubing and connectors must be properly maintained and cannot extend through walls or partitions. Gas supply outlets must be capped when not in use. 	■ Equal to State standards. ■ Equal to State standards.
MOBILEHOMES, RECREATIONAL VEHICLES AND COMMERCIAL COACHES	CCR 900, 902, 904, 908 Federal Reg. 500.135 Federal MSPA Sec. 203(b)(1)	Mobilehomes (constructed prior to June 15, 1976), recreational vehicles, and commercial coaches provided by the employer must display an insignia of approval issued by HCD. Mobilehomes constructed after June 15, 1976 must display a label indicating compliance to the Federal Mobilehome Construction and Safety Standards.	■ Equal to State Standards.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
PERMITS TO OPERATE HOUSING	CCR 626, 627, 631, 633, 634, 641 Federal MSPA. Sec. 203(a)	Operators must apply for, and obtain, a permit to operate prior to having five or more employees occupy a facility.	Operators must obtain, from an applicable local or State agency, a permit to operate prior to any migrant or seasonal worker occupying a facility.
	203(b)(1) and (2) Federal MSPA Sec. 500.135	Operators must apply for a permit at least 45 days prior to occupancy.	For FACILITIES HOUSING FEWER THAN FIVE WORKERS contact the DOL-WHD office nearest your location (see page 3).
		Permit applications must be submitted to the applicable State or local enforcement agency.	Permit (or copy) must be displayed in a conspicuous place at the housing facility.
		Permit (or copy) must be displayed in a conspicuous place at the housing facility.	
POSTING OF REQUIRED INFORMATION	CCR 624, 625 Federal MSPA Reg. Sec. 500.75(f), 500.75(g)	The following must be posted in a conspicuous place at the facility through the duration of the housing use: • Information Notice from the enforcement agency • Permit to operate (or copy) • Name, address and telephone number of Caretaker	The following must be posted in a conspicuous place at the facility through the duration of the housing use: • Permit to operate (or copy) • Name, address of housing provider and caretaker • Mailing address and telephone number of the facility. • Terms and conditions of housing.
SCREENS	CCR 728 Federal OSHA Reg. 1910.142(b)(8), 1910.142(d)(2)	Windows that open to the outside in rooms used for living, dining, cooking, sleeping purposes, bathing and toilet facilities must be maintained with insect screening of less that 16 mesh per inch material. Exterior door openings must have insect-proof screen doors or solid doors with self-closing devices.	▼ Equal to State standards
SEWAGE	CCR 784-792	Facilities must be provided for disposal of sewage.	■ Equal to State standards
	Federal OSHA Reg. 1920.142(e) Federal MSPA Reg.	Waste liquids cannot be permitted to collect on the ground.	In addition
	500.134	Traps, vents, lines, and drains related to underground septic tanks, and sewage systems must be covered, structurally sound, maintained and water tight.	Facilities must be connected to public sewer lines, if available.

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
TENTS	CCR 910 Federal MSPA Sec. 203(a) Federal MSPA Sec. 500.134	Floors must meet the following requirements:	■ Use State Standards
TOILETS	CCR 760-766 Federal OSHA Reg. 1910.142(a)(4), 1910.142(d)	TYPE: Water flush toilets are generally required and may be combined with urinals. Other systems, such as chemical toilets, may be used with written approval from the local health department.	▼ TYPE: Equal to State Standards
		LOCATION: Use Federal standards.	LOCATION: Toilet facilities must be located within 200 feet of living units. In addition Privies/chemical toilets, (when permitted by local health departments), cannot be located closer than 100 feet to living unit.
		QUANTITY: One toilet for each 10 occupants of each sex for facilities constructed after February 22, 1973. One toilet for each 15 occupants in facilities constructed before February 22, 1973. • Toilets shall be clearly identified for "MEN" or "WOMEN". The use of proper symbol is permitted.	◀QUANTITY: Equal to State standards
		Urinals: One of every three required toilets may be substituted with an approved urinal in toilet rooms designed for men.	 ✓ URINALS: Use State Standards. <u>In addition</u> Urinals must be provided; ratio at one unit for each 25 men.
		MAINTENANCE: Use and repairs cannot be hazardous to public health, safety, or welfare. Plumbing systems must be kept clean and in good working order.	 ■ MAINTENANCE: Equal to State Standards In addition toilet paper must be provided facilities must be cleaned daily lights must be on in toilet room during dark hours

SUBJECT	CODE/REGULATION AUTHORITY	STATE	FEDERAL
WATER SUPPLY	CCR 770, 772, 774 Federal OSHA Reg. 1910.142(c),1910.142(f)(3),	MIANTAINANCE: Supply system and distribution lines must be maintained to provide service at normal operating pressure to all fixtures.	■ MAINTENANCE: Equal to State Standards
	1910.142(i),1910.142(i)(3),	QUALITY: Drinking water must be potable. Testing by the local health department is required annually, also when major repairs or alterations have been made to the system or when purity is questioned. Hot and cold water under pressure required for cooking and bathing facilities. Any toilet or other plumbing fixture shall be maintained to prevent siphonage of water back into the water system.	■ QUALITY: Equal to State Standards
		AVAILABILITY: Exterior faucets must be placed at suitable and convenient locations. Common drinking cups are not allowed.	▲ AVAILABILITY: Equal to State Standards <u>In addition</u>
			Drinking fountain is required if camp has water pressure.
		QUANTITY: Use Federal standards.	QUANTITY: Minimal requirement is 35 gallons a day for each person with peak rate at 2 ½ times average hourly demand.
		STORAGE: Storage tanks or receptacles must be clean and covered	■ STORAGE: Equal to State Standards