STATE OF CALIFORNIA DEPARTMENT OF HOUSING AND COMMUNITY DEVELOPMENT DIVISION OF CODES AND STANDARDS

PRIVATE FIRE HYDRANT TEST AND CERTIFICATION REPORT

ALL PARKS MUST RETURN THIS FORM TO THE ENFORCEMENT AGENCY FOR THE PARK (SEE THE REVERSE SIDE FOR INSTRUCTIONS ON COMPLETING THIS FORM)

	• IDENTIFICATION ame:			Park ID#					
Park Ad	ddress:								
City: CA ZIP:									
Park Operator Name Phone Number									
Park Operator Address and City									
Part 2 -	CERTIFICATION	EXCEPTIONS -	You do not need certific	cation, but must	complete	this section	on if any of the	following applies:	
Hydrants are publicly owned and maintained - Water Company Name									
No hydrants and park was built before September 1, 1968 - List Date of Construction: / /									
No hydrants and park has 14 or less total lots - Enter Number of Lots:									
🗌 No	private hydrants	s and park wa	s built after Septembe	er 1, 1968. (Spe	ecific exc	eption at	the time of co	instruction.)	
(St. 1. Hyd 2. All H 3. Who 4. Aro 5. All H (Sta 6. Eac 7. Eac Verific I verify	Irant stems and hydrant threads ere subject to v und all hydrants hydrants outlets andpipe outlets n h hydrant is cle h 1 ½ -inch hydr All "NO" a cation: y under penalty	onsidered hyd I valves opera a and caps are ehicular dama s is a minimul s are 14 inche eed not be a sp early identified drant has an a answers are of perjury tha	drants for these require the fully, freely, and a e undamaged. age, hydrants are phy m of 36 inches of und s to 24 inches above becific height, but must l or marked. approved hose in a m violations and will p t either this park is e	re properly lub ysically protect obstructed acce grade. be readily acces narked enclosu prohibit the is	ed. ess. sible.) re.	of the p	NO	• Operate.	
from testing requirements or the hydrant operation is in compliance.					Park owner or operator				
Part 4 – Five-Year Fire Hydrant Water Flow Test					To be completed by authorized certifier ONLY.				
1 2 3	Barrel Size (inches) Fc		Pressure (PSI) HYDRANTS IN THE PARK, J			USING THE		Pressure (PSI) 	
PART 5 -		OF TEST RESU	LTS						
Certifier	Name				_License	e Class a	ind No:		
Address									
Telephone NumberE-Mai					Address				
Printed Name				Title					
Signatu	re			Date o	f Test		/ /		
			SE OF EXISTING SYSTEN					Y	
Badge	Number		Signature						

INSTRUCTIONS FOR COMPLETING HCD MP 532*

Return the completed form to the Area Office that issues your permit to operate with a copy to your local fire district

Northern Area Office 9342 Tech Center Drive, Suite 550 Sacramento, CA 95826 Southern Area Office 3737 Main Street, Suite 400 Riverside, CA 92501

PART 1 - IDENTIFICATION

Park ID# - Enter the park Identification Number as shown on the permit to operate.

Park Name - Enter the name of the park as shown on the permit to operate.

Park address - Enter the physical address of the park.

Enter Park Operator Name, phone number, and address.

PART 2 - CERTIFICATION EXCEPTIONS – These certification requirements do not apply to:

- Parks with public hydrants, where the local water district owns the water or hydrant system and performs regular hydrant testing. List the name of the water company.

- Parks, without hydrants, constructed prior to September 1, 1968.
- Parks, without hydrants, with 14 or less total spaces.

- Parks, <u>without hydrants</u>, constructed after September 1, 1968.

All parks with hydrants must have them tested and certified regardless of park size or date of construction. THE PARK OWNER/OPERATOR'S SIGNATURE VERIFYING AN EXCEPTION IS REQUIRED IN PART 3.

PART 3 - ANNUAL FIRE HYDRANT OPERATION TEST **

Initial the appropriate column to indicate whether the hydrant(s):

- 1. stems and valves fully operate, open and close freely, and have the proper lubrication.
- 2. caps, seals and threads are undamaged.
- 3. which are subject to vehicular damage, are provided physical protection.
- 4. has a minimum of 36 inches of clear space around all hydrants.
- 5. outlets are between 14 & 24 inches above grade. Standpipe outlets need not be a specific height, but must be readily accessible.
- 6. is clearly identified or marked for easy location in an emergency.
- 7. that are 1 ½ inch, have a 75-foot hose on a rack, or reel contained in an enclosed cabinet marked "FIRE HOSE" in 4-inch contrasting letters.

The operational test may be verified by a park owner/operator during the four years between the five-year water flow certification. If the park performs the operational test, the owner/operator's signature verifying compliance is required. During the five-year test, <u>only</u> the entity performing the water flow test may certify the operational test.

PART 4 - FIVE-YEAR FIRE HYDRANT WATER FLOW TEST (To only be completed every five years by a certified person) ** **Barrel size** – Enter the barrel or riser diameter measured in inches.

Flow – Enter the measured flow in gallons per minute.

Pressure – Enter the residual pressure measured in pounds per square inch.

PART 5 - CERTIFICATION OF TEST RESULTS

This section is to be completed by the fire agency responsible for fire suppression in the park, local water supplier, Licensed Fire Protection Engineer, or C-16 Fire Protection Contractor witnessing and certifying the test information.

Certifier Name – Enter the name of the person, agency or entity certifying the test results.

Contractor's classification and number – Enter the California Contractors State License Board classification and license number or the license number for a California licensed fire protection engineer.

Address - Enter the address of the person, agency, or entity certifying the test results.

Telephone Number - Enter certifiers' telephone number.

E-Mail Address – Enter certifiers' e-mail address, if available.

Name - Print the name of the person certifying the test.

Title – Enter the title of the person certifying the test.

Signature – Required signature of person certifying test.

Date – Enter the date of the certification.

PART 6 - APPROVAL FOR CONTINUED USE OF EXISTING SYSTEM – COMPLETED BY LOCAL FIRE AGENCY ONLY. This section may only be completed by a local fire agency when a private fire hydrant cannot be repaired to meet these standards, given local conditions, and the fire agency responsible for fire suppression in the park approves its continued use or use of alternative fire protection methods.

*Refer to Title 25, California Code of Regulations, Article 6, commencing with Section 1300 and/or 2300.

****VIOLATIONS:** If any answers in Part III – *Annual Fire Hydrant Operation Test* are "No," and/or the *Five-Year Fire Hydrant Flow Test* of Part IV does not meet the minimum requirements, the park is in violation. The park operator/owner is responsible for correction of violations. Failure to correct violations may result in the park not being eligible to renew its annual permit to operate.